




The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

**CERTIFIED COPY OF
PRIORITY DOCUMENT**



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

W. Evans

Dated 21 May 2001

An Executive Agency of the Department of Trade and Industry

Best Available Copy


THIS PAGE BLANK (USPTO)

6 OCT 2000

The
Patent
Office

7/77

**Statement of inventorship and of
right to grant of a patent**



The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

2. Patent application number
(If you, know it)

0024463.2

3. Full name of the or of each applicant

ROKE MANOR RESEARCH LIMITED

4. Title of the invention

IMPROVEMENTS IN OR RELATING TO PACKET SWITCHES

5. State how the applicant(s) derived the right
from the inventor(s) to be granted a patent

By provisions of contract of service and Section 39(1) (a) and (b) of
the Patent Act 1977.

6. How many, if any, additional Patents Forms
7/77 are attached to this form?
(see note (c))

2

I/We believe that the person(s) named over the page (and on any
extra copies of this form) is/are the inventor(s) of the invention
which the above patent application relates to.

Signature

M Mackett
Margaret Mackett

Date 04/10/00

8. Name and daytime telephone number of
person to contact in the United Kingdom

Margaret Mackett - 01344 396808

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please give the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Patents Form 7/77

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

DAVIS, Simon Paul
17 Westering
Romsey
Hants
SO51 7LX

Patents ADP number (if you know it): 5873773002

REEVE, Andrew
47 Western Road
Winchester
Hants
SO22 5AH

Patents ADP number (if you know it): 7632888001

Reminder

Have you signed the form?


Patents ADP number (if you know it):

6 OCT 2000

The
Patent
Office

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



060CT00 E573910-1 D00393
P01/7700 0.00-0024463.2

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

2000P04863/GB/R76/MM/rh

2. Patent application number

(The Patent Office will fill in this part)

0024463.2

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ROKE MANOR RESEARCH LIMITED

Roke Manor
Old Salisbury Lane
Romsey
Hants SO51 0ZN

Patents ADP number (if you know it)

5615455005

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

IMPROVEMENTS IN OR RELATING TO PACKET SWITCHES

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Siemens Shared Services Limited
Intellectual Property Department
Siemens House, Oldbury
Bracknell, Berkshire RG12 8FZ
United Kingdom

Patents ADP number (if you know it)

7761000002

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

GB

0012611.0

25/05/00

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form -
Description 11
Claim(s) 2
Abstract 1
Drawing(s) 2x2

10. If you are also filing any of the following, state how many against each item.

Priority documents -
Translations of priority documents -
Statement of inventorship and right to grant of a patent (Patents Form 7/77) 3✓
Request for preliminary examination and search (Patents Form 9/77) 1✓
Request for substantive examination (Patents Form 10/77) -
Any other documents (please specify) -

11.

I/We request the grant of a patent on the basis of this application.

Signature

Margaret Mackett

Date 4/10/00

12. Name and daytime telephone number of person to contact in the United Kingdom

Margaret Mackett - 01344 396808

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

IMPROVEMENTS IN OR RELATING TO PACKET SWITCHES

The present invention relates to improvements in or relating to packet switches, and is more particularly concerned with cross-bar switches having a
5 cell-level scheduling scheme for handling multicast traffic therein.

Data is transferred over the Internet by means of a plurality of packet switches in accordance with a standard protocol known as Internet Protocol (IP). IP is a protocol based on the transfer of data in variable sized portions known as packets. All Internet traffic involves the transportation of packets
10 of data. Packet switches are devices for accepting incoming packets; temporarily storing each packet; and then forwarding the packets to another part of the network. In particular, a packet switch receives packets of data on a plurality of input ports and transfers each packet to a specific one of a plurality of output ports. The packets of data can be of variable length or of
15 fixed length.

Traffic volume in the Internet is growing exponentially, almost doubling every 3 months. The current capacity of internet protocol (IP) routers or packet switches is insufficient to meet this demand and hence there is a need for IP routers that can route IP traffic at extremely large aggregate
20 bandwidths in the order of several Terabit/s. Such routers are termed "Terabit Routers".

Two important trends are also evident. First, operators are consolidating all traffic onto a single IP back-bone. Secondly, IP is increasingly required to support real-time and multimedia traffic. This means
25 that the next generation of routers must also support 'Quality of Service' (QoS). In particular, they must support low bounded delay for real-time traffic.

The packets transferred in accordance with IP can (and do) vary in size. Within routers it has been found useful to pass data in fixed sized units. In routers the data packets are partitioned into small fixed sized units, known as cells.

5 One suitable technique for implementing a scalable communications path is a backplane device, known as a cell based cross-bar. Data packets are partitioned into cells by a plurality of ingress means for passage across the cross-bar.

10 The plurality of ingress means provide respective interfaces between incoming communications channels carrying incoming data and the backplane. Similarly, a plurality of egress means provide respective interfaces between the backplane and outgoing communications channels carrying outgoing data.

15 A general terabit router architecture bears some similarity to conventional router architecture. Packets of data arrive at input port(s) of ingress means and are routed as cells across the cross-bar to a predetermined egress means which reassembles the packets and transmits them across its output port(s). Each ingress means maintains a separate packet queue for each egress means.

20 The ingress and egress means may be implemented as line interface cards (LICs). Since one of the functions regularly undertaken by the ingress and egress means is forwarding, LICs may also be known as 'forwarders'. Further functions include congestion control and maintenance of external interfaces, input ports and output ports.

25 In a conventional cell based cross-bar each ingress means is connected to one or more of the egress means. However, each ingress means is only capable of connecting to one egress means at any one time. Likewise,

each egress means is only capable of connecting to one ingress means at a time.

All ingress means transmit in parallel and independently across the cross-bar. Furthermore cell transmission is synchronised with a cell cycle,
5 having a period of, for example, 108.8ns.

The ingress means simultaneously each transmit a new cell with each new cell cycle.

The pattern of transmissions from the ingress means across the cross-bar to the egress means changes at the end of every cell cycle.

10 The co-ordination of the transmission and reception of cells is performed by a cross-bar controller.

A cross-bar controller is provided for efficient allocation of the bandwidth across the cross-bar. It calculates the rates that each ingress means must transmit to each egress means. To support multicast traffic, it is
15 also necessary to calculate the multicast rates from ingress means to all relevant egress means. This is the same as the rate at which data must be transmitted from each packet queue. The calculation makes use of real-time information, including traffic measurements and indications from the ingress means. The indications from the ingress means include monitoring the
20 current rates, queue lengths and buffer full flags. The details of the calculation are discussed more rigorously in the copending UK Patent Application Number 9907313.2 (docket number F21558/98P4863).

The cross-bar controller performs a further task; it serves to schedule the transfer of data efficiently across the cross-bar whilst maintaining the
25 calculated rates. At the end of each cell cycle, the cross-bar controller communicates with the ingress and egress means as follows. First, the cross-bar controller calculates and transmits to each ingress means the identity of

the next packet queue from which to transmit. Secondly, the cross-bar controller calculates and transmits to each egress means the identity of the ingress from which it must receive.

By allowing many egress means to receive from the same ingress means at the same time, multicast replication can be achieved.

In accordance with one aspect of the present invention, there is provided a method of operating a packet switch which comprises a plurality of ingress means, a plurality of egress means, a cross-bar and a controller, the cross-bar being connected between the ingress means and the egress means to transfer multicast and unicast data traffic from the ingress means to the egress means, the method comprising the steps of:-

- a) determining if the data traffic to be transferred is unicast or multicast;
- b) if the data traffic is unicast, invoking a unicast schedule;
- 15 c) if the traffic is multicast, invoking a multicast schedule; and
- d) transferring the data traffic in accordance with the invoked schedule.

Advantageously, step c) comprises forming a multicast cell fanout table containing current fanout requirements for a cell at the head of a multicast queue in each ingress means.

Step c) further comprises setting eligible bits for multicast cells which are currently allowed to be scheduled.

Step c) further comprises determining a priority for each ingress means for sending the cells.

25 The method further comprises the step of e) filling a blank multicast schedule in accordance with the priority assigned to each ingress means.

Step e) comprises the step of:-

(i) filling the blank schedule with the full fanout of the first priority ingress means.

Step e) further comprises the step of:-

(ii) filling in as much of the fanout of the next priority ingress means and subsequent ingress means as possible to complete the schedule.

Step (ii) comprises selecting fanouts of ingress means in accordance with multicast egress credit allocated to each egress means.

The term 'fanout' as used herein refers to set of egress means to which the current cell must be replicated.

For a better understanding of the present invention, reference will now be made, by way of example only, to the accompanying drawings in which:-

Figure 1 illustrates multicast ingress rate resolution; and

Figure 2 illustrates multicast scheduling.

The desired features for a multicast scheme in accordance with the present invention are listed below:

- High efficiency (aim for 70-80% pure multicast traffic or better)
- Use shared cross-bar for replication
- Easily integrated into the unicast cell level scheduling algorithm
- Fair across ingress ports to each egress port
- Supports real time and non real time multicast services
- Maintains unicast bandwidth commitments

It is assumed that there is one multicast IP packet (or fixed length part of such a packet) available to be sent at each ingress line interface card (LIC).

Although the present invention will be described with reference to LICs, it will readily be appreciated that it is not limited to using LICs and that any suitable device which provide the ingress and egress functions can be used.

The fanout of a multicast packet is defined to be the set of egress ports (of the cross connect) to which the packet must be replicated. The fanout of the next multicast cell must be known by the central scheduler in order that it can be scheduled across the cross connect.

5 It is assumed that the fanout information for the next multicast cell to be sent from each ingress port is known.

 Once ingress bandwidths have been allocated for multicast traffic, scheduling opportunities must be allocated for all ingress LICs to ensure fair access and to preserve allocated rates. The basic scheduling concept for
10 multicast slots is shown in Figure 1.

 Figure 1 illustrates separate ingress lines (Figure 1a) and a multicast schedule (Figure 1b).

 The four ingress lines are labelled 0 to 3 as shown on the left. Each line has a rate associated with multicast traffic, that is, high and low priority
15 queues. This rate is represented as a send opportunity, indicated by the arrows, every fixed number of cell periods. Ingress line 1 has the highest rate in that it provides a send opportunity every two cell periods. Ingress line 0 has a rate which provides a send opportunity every four cell periods. Ingress line 2 has the same rate as ingress line 0 but is out of phase with it by a cell
20 period. Ingress line 3 has the lowest rate – providing a send opportunity every sixteen cell periods.

 The send opportunities of ingress lines 0 to 3 as shown in Figure 1a are combined into a multicast schedule as shown Figure 1b. In accordance with the present invention, the send opportunities are combined by placing a
25 send opportunity on the next free cell cycle (cell cycles are numbered 1 to 16 as shown) unless it would overlap with the next send opportunity for the

same ingress LIC. This means that each ingress has send opportunities as shown in Table 1 below:-

Table 1.

	Cell cycles															
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
0			√				√				√				√	
1	√		√		√		√		√		√		√		√	
2		√				√				√				√		
3								√								

5

However, in order to combine these send opportunities in accordance with the present invention, this means that each ingress will send in the free cell cycles as shown in Table 2:-

10 **Table 2.**

	Cell cycles															
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
0			√				√					√			√	
1	√			√	√			√		√		√	√			
2		√				√					√			√		
3									√							√

15

It can readily be seen from Table 2 above and from Figure 1b that cell period 12 has two send opportunities where the send opportunity for ingress LIC 1 has to be stacked on top of the cell send opportunity for ingress LIC 0 to avoid it colliding with its next send opportunity. This means that, for cell 12, LIC 1 must be transmitted before LIC 0, that is, LIC 1 is first choice and LIC 0 is second choice. It will be appreciated that LIC 1 has to be first choice as it will collide with itself on the next available cell cycle.

20

The net effect of this process is to spread the multicast send opportunities on as many cell periods as possible thus reducing the height of

each stack. The height of each stack is directly related to the number of ingress multicast cells that have to be scheduled in this cycle and thus the amount of sorting that has to be carried out by the algorithm.

5 Whilst minimising the amount of work to be carried out in each cell cycle by the multicast scheduler, the maximum jitter is also limited to $1/\text{rate}$. A cell send opportunity is never delayed by more than the gap between the ideal ingress cell send opportunities, thus making the jitter inversely proportional to the rate. Multicast real time delay jitter can thus be improved by allocating higher rates.

10 If there is no multicast cell send opportunity scheduled, then a normal unicast scheduling algorithm is invoked. If there is one or more multicast cell send opportunities then a multicast scheduling algorithm is invoked in accordance with the present invention.

15 Figure 2 shows the active components in the multicast scheduling algorithm. A multicast cell fanout table is shown in Figure 2a which contains the current fanout requirements for the cell at the head of the multicast queue in each ingress LIC. The table comprises an ordered list of pointers relating to the stack of multicast send opportunities on a particular cell period. The ingress LICs are listed on the left of the table and the egress LICs are listed
20 on the top of the table. As shown, ingress 0 is sending to egresses 0, 2, 4, 6, 8 and 10, ingress 1 is sending to egresses 2, 3, 4, 9 and 10, ingress 3 is sending to egresses 9 and 10, and ingress 6 is sending to egresses 5, 6, 9 and 10.

25 When the multicast schedule as shown in Figure 1b is carried out for these specific examples, it is found that ingress 1 is the first choice and ingress 6 is the second choice. This means that ingress 1 has first priority to send a multicast cell followed by ingress 6.

Each egress has a multicast credit as shown in Figure 2b. The multicast egress credit is determined in accordance with a multicast bandwidth allocation method as described in co-pending British patent application no. 0018328.5 (docket number 2000P04909). The egress credit is the maximum number of multicast cells that can be sent to each egress in one bandwidth allocation period (BAP). A BAP is the number of cell cycles over which the calculated rate remains static, that is, the calculated rate may change ever BAP. As shown in Figure 2b, egress 0 has a credit of 27, egress 1 has no credit and egresses 2 and 3 have credits of 35 and 5 respectively.

As the algorithm supports the concept of scheduling part of the fanout and leaving residues, the entries in the multicast cell fanout table will change, that is, 1s will go to 0s when they have been scheduled, when part of the fanout has been scheduled. Another table (not shown) is thus required to remember the full fanout for the duration of the packet. This second table, called the multicast packet fanout table, is updated when the next fanout is sent to a traffic management card in the controller at the end of the packet.

The algorithm starts with a blank schedule and fills this with the full fanout of the first choice ingress LIC, as shown on the right of Figure 2d in the compilation of the control frame. In this case, ingress LIC 1 is the first choice and 1s have been entered in the control frame corresponding to egresses 2, 3, 4, 9 and 10 leaving the remaining positions blank. It then moves to the next ingress LIC of choice and schedules as much of the fanout as possible. In the example illustrated in Figure 2a, the second choice is ingress LIC 6. In this case, as egress LICs 9 and 10 have been taken up with the fanout for the first choice, only egress LICs 5 and 6 can be added to the control frame. This is shown as 6s in the control frame of Figure 2e in the positions corresponding to egress LICs 5 and 6.

It will be appreciated that this will be repeated for subsequent choice ingress LICs until the control frame is as full as it can be. For example, if ingress LIC 0 is the third choice, 0s will be added to the control frame to correspond to egress LICs 1 and 8. Ingress LIC 3 cannot add anything to the control frame as the two egress LICs to which it is to multicast are already taken by the first choice ingress LIC, that is, ingress LIC 1. Although ingress LIC 2 has a cell which can be transmitted to egress LIC 1, this cannot be added to the control frame as there is no multicast egress credit as will be described more fully below. A fully compiled control frame for the example shown in Figure 2 may comprise the following:-

| 0 | | 1 | 1 | 1 | 6 | 6 | | 0 | 1 | 1 | |

For the multicast cells that are scheduled for this cell period, that is, cells from ingress LICs 1 and 6 in this example, the eligible bits are set. As shown in the 'eligible' status column (Figure 2c), ingresses 0, 1, 2 and 6 are eligible for multicast as shown by the 1s. Ingress 3 is not eligible for multicast as shown by the 0. These bits are only reset when the cell has been scheduled for the complete fanout. In the example, shown in Figure 2, only ingress LIC 1 will be reset as that is the only ingress LIC which has been completely scheduled for the whole fanout.

The algorithm will then attempt to schedule as many of the other multicast cells as possible, starting with the one whose ingress LIC number is one larger than the first choice, subject to two constraints. The first is that the eligible bit is set, the second is that the multicast egress credit is positive for a particular egress destination. The attempt to schedule as many other multicast cells as possible is cyclic in nature and once all ingress lines in the multicast cell fanout table have been evaluated for scheduling from the first

choice ingress line, the algorithm returns to the top of the fanout table and carries on until all ingress line entries have been evaluated.

Any gaps in the compiled frame can be filled by unicast traffic.

5 The multicast egress credit is decremented each time a multicast cell is scheduled for that particular egress. In a real implementation there will probably be separate credit for real time multicast cells and for non real time multicast cells. This credit can be refreshed by the equivalent allocated egress rates every BAP period or on a sub-multiple of a BAP period depending on the amount of egress smoothing desired.

CLAIMS:

1. A method of operating a packet switch which comprises a plurality of ingress means, a plurality of egress means, a cross-bar and a controller, the cross-bar being connected between the ingress means and the egress means to transfer multicast and unicast data traffic from the ingress means to the egress means, the method comprising the steps of:-

- a) determining if the data traffic to be transferred is unicast or multicast;
- b) if the data traffic is unicast, invoking a unicast schedule;
- c) if the traffic is multicast, invoking a multicast schedule; and
- d) transferring the data traffic in accordance with the invoked schedule.

2. A method according to claim 1, wherein step c) comprises forming a multicast cell fanout table containing current fanout requirements for a cell at the head of a multicast queue in each ingress means.

3. A method according to claim 2, wherein step c) further comprises setting eligible bits for multicast cells which are currently allowed to be scheduled.

4. A method according to claim 3, step c) further comprises determining a priority for each ingress means for sending the cells.

5. A method according to claim 4, wherein the step of determining the priority for each ingress means is based on the combination of send opportunities.
6. A method according to claim 4 or 5, further comprising the step of e) filling a blank multicast schedule in accordance with the priority assigned to each ingress means.
7. A method according to claim 6, wherein step e) comprises the step of:-
 - (i) filling the blank schedule with the full fanout of the first priority ingress means.
8. A method according to claim 7, wherein step e) further comprises the step of:-
 - (ii) filling in as much of the fanout of the next priority ingress means and subsequent ingress means as possible to complete the schedule.
9. A method according to claim 8, wherein step (ii) comprises selecting fanouts of ingress means in accordance with multicast egress credit allocated to each egress means.
10. A method of operating a packet switch substantially as hereinbefore described with reference to the accompanying drawings.

ABSTRACT
IMPROVEMENTS IN OR RELATING TO PACKET SWITCHES

The invention relates to cell level scheduling for handling multicast traffic in routing devices, for example cross-bar switches. The routing device has a plurality of ingress line interface cards (LICs), a plurality of egress LICs, a cross-bar and a controller. Multicast and unicast data traffic passes from the ingress LICs via the cross-bar to the egress LICs. A given multicast data packet is sent from a given ingress LIC to a predetermined set of egress LICs known as the fanout of the given packet. Each ingress LIC has an associated rate of send opportunities. The inventive method allows multicast send opportunities to be spread as evenly as possible over cell periods. The method also invokes a conventional unicast scheduling scheme when no multicast send opportunity is scheduled and a multicast scheduling scheme when one or more multicast send opportunities are present. The schedule is filled out with the fanouts of multicast packets in accordance with the send priority associated with the respective ingress LICs upon which each of the respective multicast packets is queued.

(Fig. 2)

Ingress




Fig. 1a

Multicast
Schedule




Fig. 1b

THIS PAGE BLANK (USPTO)

Fig. 2c

Multicast Cell Fanout Table

		Egress											Ingress
		0	1	2	3								
1st Choice	0	1	0	1	0	1	0	1	0	1	0	1	0
	1	0	0	1	1	1	0	0	0	1	1	0	1
	2	0	1	1	0	0	0	0	0	0	1	0	0
	3	0	0	0	0	0	0	0	0	1	1	0	0
2nd Choice	0	0	0	0	0	1	1	0	0	1	1	0	0
	1	0	0	0	0	0	0	0	0	0	0	0	0
	2	0	0	0	0	0	0	0	0	0	0	0	0
	3	0	0	0	0	0	0	0	0	0	0	0	0

Fig. 2a

Fig. 2d

Fig. 2e

Fig. 2f

Fig. 2g

Fig. 2h

Fig. 2i

Fig. 2j

Fig. 2k

Fig. 2l

Fig. 2m

Fig. 2n

Fig. 2o

Fig. 2p

Fig. 2q

Fig. 2r

Fig. 2s

Fig. 2t

Fig. 2u

Fig. 2v

Fig. 2w

Fig. 2x

Fig. 2y

Fig. 2z

Fig. 2aa

Fig. 2ab

Fig. 2ac

Fig. 2ad

Fig. 2ae

Fig. 2af

Fig. 2ag

Fig. 2ah

Fig. 2ai

Fig. 2aj

Fig. 2ak

Fig. 2al

Fig. 2am

Fig. 2an

Fig. 2ao

Fig. 2ap

Fig. 2aq

Fig. 2ar

Fig. 2as

Fig. 2at

Fig. 2au

Fig. 2av

Fig. 2aw

Fig. 2ax

Fig. 2ay

Fig. 2az

Fig. 2ba

Fig. 2bb

Fig. 2bc

Fig. 2bd

Fig. 2be

Fig. 2bf

Fig. 2bg

Fig. 2bh

Fig. 2bi

Fig. 2bj

Fig. 2bk

Fig. 2bl

Fig. 2bm

Fig. 2bn

Fig. 2bo

Fig. 2bp

Fig. 2bq

Fig. 2br

Fig. 2bs

Fig. 2bt

Fig. 2bu

Fig. 2bv

Fig. 2bw

Fig. 2bx

Fig. 2by

Fig. 2bz

Fig. 2ca

Fig. 2cb

Fig. 2cc

Fig. 2cd

Fig. 2ce

Fig. 2cf

Fig. 2cg

Fig. 2ch

Fig. 2ci

Fig. 2cj

Fig. 2ck

Fig. 2cl

Fig. 2cm

Fig. 2cn

Fig. 2co

Fig. 2cp

Fig. 2cq

Fig. 2cr

Fig. 2cs

Fig. 2ct

Fig. 2cu

Fig. 2cv

Fig. 2cw

Fig. 2cx

Fig. 2cy

Fig. 2cz

Fig. 2da

Fig. 2db

Fig. 2dc

Fig. 2dd

Fig. 2de

Fig. 2df

Fig. 2dg

Fig. 2dh

Fig. 2di

Fig. 2dj

Fig. 2dk

Fig. 2dl

Fig. 2dm

Fig. 2dn

Fig. 2do

Fig. 2dp

Fig. 2dq

Fig. 2dr

Fig. 2ds

Fig. 2dt

Fig. 2du

Fig. 2dv

Fig. 2dw

Fig. 2dx

Fig. 2dy

Fig. 2dz

Fig. 2ea

Fig. 2eb

Fig. 2ec

Fig. 2ed

Fig. 2ee

Fig. 2ef

Fig. 2eg

Fig. 2eh

Fig. 2ei

Fig. 2ej

Fig. 2ek

Fig. 2el

Fig. 2em

Fig. 2en

Fig. 2eo

Fig. 2ep

Fig. 2eq

Fig. 2er

Fig. 2es

Fig. 2et

Fig. 2eu

Fig. 2ev

Fig. 2ew

Fig. 2ex

Fig. 2ey

Fig. 2ez

Fig. 2fa

Fig. 2fb

Fig. 2fc

Fig. 2fd

Fig. 2fe

Fig. 2ff

Fig. 2fg

Fig. 2fh

Fig. 2fi

Fig. 2fj

Fig. 2fk

Fig. 2fl

Fig. 2fm

Fig. 2fn

Fig. 2fo

Fig. 2fp

Fig. 2fq

Fig. 2fr

Fig. 2fs

Fig. 2ft

Fig. 2fu

Fig. 2fv

Fig. 2fw

Fig. 2fx

Fig. 2fy

Fig. 2fz

Fig. 2ga

Fig. 2gb

Fig. 2gc

Fig. 2gd

Fig. 2ge

Fig. 2gf

Fig. 2gg

Fig. 2gh

Fig. 2gi

Fig. 2gj

Fig. 2gk

Fig. 2gl

Fig. 2gm

Fig. 2gn

Fig. 2go

Fig. 2gp

Fig. 2gq

Fig. 2gr

Fig. 2gs

Fig. 2gt

Fig. 2gu

Fig. 2gv

Fig. 2gw

Fig. 2gx

Fig. 2gy

Fig. 2gz

Fig. 2ha

Fig. 2hb

Fig. 2hc

Fig. 2hd

Fig. 2he

Fig. 2hf

Fig. 2hg

Fig. 2hh

Fig. 2hi

Fig. 2hj

Fig. 2hk

Fig. 2hl

Fig. 2hm

Fig. 2hn

Fig. 2ho

Fig. 2hp

Fig. 2hq

Fig. 2hr

Fig. 2hs

Fig. 2ht

Fig. 2hu

Fig. 2hv

Fig. 2hw

Fig. 2hx

Fig. 2hy

Fig. 2hz

Fig. 2ia

Fig. 2ib

Fig. 2ic

Fig. 2id

Fig. 2ie

Fig. 2if

Fig. 2ig

Fig. 2ih

Fig. 2ii

Fig. 2ij

Fig. 2ik

Fig. 2il

Fig. 2im

Fig. 2in

Fig. 2io

Fig. 2ip

Fig. 2iq

Fig. 2ir

Fig. 2is

Fig. 2it

Fig. 2iu

Fig. 2iv

Fig. 2iw

Fig. 2ix

Fig. 2iy

Fig. 2iz

Fig. 2ja

Fig. 2jb

Fig. 2jc

Fig. 2jd

Fig. 2je

Fig. 2jf

Fig. 2jg

Fig. 2jh

Fig. 2ji

THIS PAGE BLANK (USPTO)